

ITEM	400E TERMINAL	400E COMPAT	531E (2480 BATCH)	4080 COMPAT	VT52 COMPAT	ADM3A COMPAT
Price	\$1200 + cabling	\$1200 + cabling	\$1500 + cabling	\$1595 + cabling	\$1400 + cabling	\$1400 + cabling
Monitor	15" - P4 (White)	15" - P4 (White)	15" - P4 (White)	15" - P39 (Green)	15" - P4 (White)	15" - P4 (White)
Keyboard	72-key detachable	72-key detachable	82-key detachable	72-key detachable	81-key detachable	72-key detachable
Character Set	64-char ASCII 95-char optional	64-char ASCII 95-char optional	95-char ASCII	95-char ASCII	95-char ASCII	95-char ASCII
Character Dot Matrix	7 x 7 w/2 descenders	7 x 7 w/2 descenders	7 x 7 w/2 descenders	7 x 7 w/2 descenders	7 x 7 w/2 descenders	7 x 7 w/2 descenders
Proms	2708/2716 E-Proms	2708/2716 E-Proms	2708/2716 E-Proms	2708/2716 E-Proms	2708/2716 E-Proms	2708/2716 E-Proms
Microprocessor	8080	8080	8080	Z80	8080	8080
Transmission	Asynchronous	Asynchronous	Asynchronous	Asynchronous	Asynchronous	Asynchronous
Interface	RS232C 20 MA Optional	RS232C 7-Bit Parallel 20 MA Optional	RS232C 20 MA Optional	RS232C 20 MA Optional	RS232C 20 MA Optional	RS232C 20 MA Optional
Baud Rates	110-9600 (Diode or Set-Up Mode Change)	110-9600 (Diode or Set-Up Mode Change)	110-9600 (Diode or Set-Up Mode Change)	110-9600 (Diode or Set-Up Mode Change)	110-9600 (Diode or Set-Up Mode Change)	110-9600 (Diode or Set-Up Mode Change)
Aux-Video (RS170-Compatible)	Yes, BNC Optional	Yes, BNC Optional	Yes, BNC Optional *BNC not available w/print	No	Yes, BNC Optional	Yes, BNC Optional
Case Options	E/D/C/R/W/D2	E/D/C/R/W/D2	E/D/W	E/W	E/D/C/R/W/D2	E/D/C/R/W/D2
Export Model 230 VAC/50 Hz	Optional	Optional	Optional	Optional	Optional	Optional
I/O Modes	Full/Half/Local	Full/Half/Local	Full/Half/Local	Full/Half/Local	Full/Half	Full/Half
Display Modes	Roll/Scroll/Page	Roll/Page	Roll/Page	Roll/Page	Roll	Roll
Memory Size						
Standard	2000 Chars	1920 Chars (2480) 960 Chars (2440) 1280 Chars (1680) 512 Chars (1632)	1920 Chars	3200 Chars	1920 Chars	1920 Chars
Optional		256 Chars (0832)	960 Chars (2440)			
Display Format						
Standard	24 x 80 (1 Line Hid)	24 x 80 24 x 40 16 x 80 16 x 32	24 x 80	40 x 80	24 x 80	24 x 80
Optional	24 x 40 (26 Lines Hid) 12 x 40 (38 Lines Hid)	8 x 32	24 x 40			
Character Accents	Blink/Dim/Reverse	Blink/Dim/Reverse	Blink/Dim/Reverse	Blink/Dim/Reverse	None	None
Standard	*Blink only w/ U/L Case	*Blink only w/ U/L Case				

ITEM	400E TERMINAL	400E COMPAT	531E (2480 BATCH)	4080 COMPAT	VT52 COMPAT	ADM3A COMPAT
Cursor Commands						
Home/Up/Down Right/Left/CR	Yes	Yes	Yes	Yes	Yes	Yes
Auto LF on CR	Optional	Optional	Optional	Optional	No	Optional
Hold at EOL	Optional	Optional	Optional	Optional	Yes	No
Set Cursor Position (Cursor Address)	Set Cursor Y ESC Y ___ Set Cursor X ESC X ___	Set Cursor X/Y SI/CPC/CPL	Set Cursor X/Y SI/CPC/CPL	Set Cursor X/Y SI/CPC/CPL	Set Cursor X/Y ESC Y___ __	Set Cursor X/Y ESC =___ __
Read Cursor Position (Cursor Sense)	Optional	No	Optional	No	No	No
Reverse LF	No	No	No	No	Yes	No
Send Page	No	No	Yes	No	No	No
Erase Commands						
Erase Memory	Yes	Yes	Yes	Yes	No	Yes
Erase Page	No	Yes	Yes	Yes	No	Yes
Erase to End-Of-Page	No	No	Yes	No	Yes	No
Erase Line	No	No	Yes	No	Yes	No
Insert/Delete Commands						
Character	No	No	Yes	No	No	No
Line	No	No	Yes	No	No	No
Set Functions						
Set Screen Position	Yes	No	No	No	No	No
Set Protect	No	No	Yes	No	No	No
Set Enter Mode	No	No	Yes	No	No	No
Set Printer Output	No	No	Yes	No	No	No
Enter Set-Up Mode	CTRL/Ø	CTRL/Ø	CTRL/Ø	CTRL/Ø	CTRL/9 on Numeric Pad	CTRL/9 on Numeric Pad
Tab	Optional (Software)	Optional (Software)	Yes in Protect Mode	Yes W/S1901 Compat Inc. Backtab	Yes Typewriter-Tab Every 8 Spaces	No
Parity	Xmits Even	Xmits Mark	Xmits Even	Xmits Even	Xmits Even	Xmits Even
Keyboard						
Layout	TTY	TTY	TTY	TTY	Typewriter	TTY
Caps Lock Key	No (Set-Up Mode Chg)	No (Set-Up Mode Chg)	No (Set-Up Mode Chg)	No (Set-Up Mode Chg)	Yes	No (Set-Up Mode Chg)
Keyboard Lock/Unlock	No	No	No	No	No	Yes
Function Keys	Optional – Up to 36	Optional – Up to 36	Optional – Up to 24	Optional – Up to 36	Optional – Up to 28	Optional – Up to 36